

Vermont Department of Labor Certificate of Wire Rope Splice or Repair Report

| Date | | | | | | | Description on Rope: | | | | |
|--------------------------------------|-----------------------------------|----------|----|--------------|---------------|--|---|---|---------------------|---------|--|
| Area Name | | | | | | | Diameter | | | | |
| Tramway Number | | | | | | | | | | | |
| | | | | | | | Construction | | | | |
| Tramway Name | | | | | | | Core | | | | |
| Slice Data: | | | | | | | Manufacturer | | | | |
| Original | | | | | | | Length of undisturbed rope to nearest splice (if addition or rework)_ | | | | |
| Original | | | | | | | | , | | | |
| Additional | | | | | | | Reason for Rework | | | | |
| Rework: | | | | | | | | | | | |
| Strand Repair for | Replace | ment: | | | | | | | | | |
| | | | | | | | | | | | |
| . 1 | l | I | | Lengt | th of Sp | lice or | Strand Replac | cement | ı | I | |
| Length | ▼ TUCK | | | | | | - | TUCK 4 | ——— | | |
| of | TUCK | _ | TU | CK 2 | | TUCK 3 | | TUCK 4 | TUCK 5 | TUCK 6 | |
| Tails | / | _ | / | | | | <u> </u> | | / | | |
| 'AAAA | UU | ŹŪ | TT | TT | III | ŦŴ | UUUU | MATTA | tititi | ĦĦ | |
| | <i> </i> + <i>+</i> | <i> </i> | | <i> </i> + + | | HH. | | | | | |
| mm | uu | \sim | m | \sim | uu | سس | Junn | mm | uuuu | mm | |
| DIRECTION OF 1 | ΓRΔVFI | | | | | | RIAGE | Type of Wrappi | ng Tails | | |
| 4 | OR MIDPOINT OF STRAND REPLACEMENT | | | | | | This splice is in accordance with the latest | | | | |
| | | | | | | | | edition of A.N.S.I. B77.1 | | | |
| Toile Ctroighton | ad | | | | | | | | | | |
| Tails Straightened DIAMETER AT TUCKS | | | | | | | | | Wire Rope Inspector | | |
| TUCK NUMBER | 3 4 5 6 | | | | 1 | | CompanyAddress | | | | |
| MAX. DIAMETER | 1 | 2 | 3 | 4 | 5 | 0 | | Auu1635 | | | |
| MIN. DIAMETER | | | | | | | 1 | | | | |